

S701

The S701 is a drive-position tyre for long-distance transportation applications. The specialised rubber tread compound provides excellent anti-scrub resistance. The varied pitch tread design and narrow horizontal grooves effectively reduce tyre noise for a more comfortable ride.



Features & Benefits:

- Three main tread grooves provide excellent handling stability for a more comfortable ride.
- Widened tread-to-road contact surface evens out pressure for improved driving stability.
- Narrow grooves are optimized to reduce noise emissions.

| Size | L.I. | S.R. | P.R. | T.D. | RIM | O.D. | S.W. | Std. RIM | L.C.C. | | RR | WG | NG DB | NG |
|-------------|------------------|------|------|------|------|------|------|----------|----------|----------|----|----|-------|----|
| | | | | | | | | | Single | Dual | | | | |
| | | | | | | | | | kg | kg | | | | |
| 295/80R22.5 | 152/148 | M | 16PR | 17.5 | 22.5 | 1044 | 298 | 9 | 3550@850 | 3150@850 | E | B | 74 | 2 |
| 315/70R22.5 | 152/148 | M | 16PR | * | 22.5 | * | * | * | * | * | D | B | 74 | 2 |
| 315/70R22.5 | 154/150(152/148) | L(M) | 18PR | * | 22.5 | * | * | * | * | * | D | B | 74 | 2 |
| 315/80R22.5 | 154/150 | M | 16PR | 18.5 | 22.5 | 1076 | 312 | 9 | 3750@825 | 3350@825 | D | B | 74 | 2 |
| 315/80R22.5 | 156/150(154/150) | L(M) | 18PR | 18.5 | 22.5 | 1076 | 312 | 9 | 4000@850 | 3350@850 | D | B | 76 | 4 |

* Data available on request